

Superluminescent Diodes are semiconductor emitters combining the high brightness of laser diodes with a broad spectrum of LEDs. They are light sources of choice for numerous applications based on low coherence measurements, spectroscopy, low speckle illumination, and others.

Superlum offers a wide range of SLD modules and SLD-based light sources. Please also check our SLD controllers and light source modules to ensure safe and stable SLD operation in your system.

Specifications (Nominal Emitter Stabilization Temperature +25 °C)


Parameter	MIN	TYP	MAX
S670.10.1			
Output power, P_{op} , ex SM fiber, mW	1.0	1.5	–
Forward current at P_{op} , mA	–	100	140
Central wavelength at P_{op} , nm	660	670	680
Spectrum width at P_{op} , FWHM, nm	8	10	–
Residual spectral modulation depth [†] at P_{op} , %	–	–	2.0
Secondary coherence subpeaks ^{††} at P_{op} , dB (10 log)	–	-25	-20
Slow / fast polarization ratio (PM modules) at P_{op} , dB	–	10	–
PD monitor current ^{†††} at P_{op} , mA	0.1	–	–
S670.8.5			
Output power, P_{op} , ex SM fiber, mW	4.0	5.0	–
Forward current at P_{op} , mA	–	120	170
Central wavelength at P_{op} , nm	660	670	680
Spectrum width at P_{op} , FWHM, nm	6	8	–
Residual spectral modulation depth [†] at P_{op} , %	–	–	2.0
Secondary coherence subpeaks ^{††} at P_{op} , dB (10 log)	–	-25	-20
Slow / fast polarization ratio (PM modules) at P_{op} , dB	–	10	–
PD monitor current ^{†††} at P_{op} , mA	0.1	–	–
S670.7.10			
Output power, P_{op} , ex SM fiber, mW	8.0	10.0	–
Forward current at P_{op} , mA	–	130	170
Central wavelength at P_{op} , nm	660	670	680
Spectrum width at P_{op} , FWHM, nm	6	7	–
Residual spectral modulation depth [†] at P_{op} , %	–	–	2.0
Secondary coherence subpeaks ^{††} at P_{op} , dB (10 log)	–	-25	-20
Slow / fast polarization ratio (PM modules) at P_{op} , dB	–	10	–
PD monitor current ^{†††} at P_{op} , mA	0.1	–	–

[†] - rated at P_{op} , decreases proportional to operating power

^{††}- direct measurements by Michelson interferometer, rated at P_{op} , lower at lower power

^{†††}- at 5 V reverse bias

Attention: all parameters are measured at optical feedback not exceeding 1E-3



Features

- Three power categories
 - 1 mW P/N S670.10.1
 - 5 mW P/N S670.8.5
 - 10 mW P/N S670.7.10
- Butterfly packaged with cooler and thermistor
- SMF or PMF pigtailed
- MMF upon request
- FC/APC connectors, LC/APC upon request

Applications


- optical sensors
- optical coherence tomography
- low speckle illumination
- atomic force microscopy
- others

Other Parameters – All Models


Parameter	MIN	TYP	MAX
SLD forward voltage at P_{op} , V	–	–	2.6
PD monitor bias voltage, V	–	–	5.0
Operating temperature at P_{op} , °C	-20	–	+65
Storage temperature at P_{op} , °C	-40	–	+85
Cooler current, A	–	–	2.5
Cooler current, V	–	–	3.2
Thermistor BETA, K	–	3892	–
Thermistor Resistance at 25 °C, kΩ	–	10	–

TYPICAL PERFORMANCE EXAMPLES


Light-current curve






Spectrum at rated power






Coherence at rated power



S670.10.1



S670.8.5



S670.7.10

Notes: examples demonstrate typical performance only. Actual performance may vary from sample to sample and from lot to lot. All specifications are subject to change without notice. **Coherence function is measured by Michelson interferometer.** Mirror displacement = Optical path difference / 2

Attention: SLDs are sensitive to optical feedback. The higher is the power, the stronger is the sensitivity.
All parameters are measured at optical feedback not exceeding 1E-3.

The following marking should be used for ordering:

P/N(type of fiber)

Examples : **S670.7.10S** – as rated above, SMF pigtail, FC/APC; **S670.8.5P** – as rated above, PMF pigtail, FC/APC.

MMF pigtailed SLDs are available upon request. Modules will be shipped FC/APC finished if not specified otherwise in the PO.

Superlum offers customization of its products to fit the requirements of every customer. Please get in touch with us for more details before ordering if you need customer-specific SLD parameters.